

Amendments to the Claims:

The following listing of claims replaces all prior versions, and listings, of claims in the application:

Listing of Claims:

1 – 17 (Canceled).

¹
~~18~~ (previously presented). A removable golf shoe cleat for use in a golf shoe having a sole, said sole having a plurality of sole attachment means for attachment of removable cleats, said removable golf shoe cleat comprising:

(a) a flange having an upper surface and an opposing bottom surface that distributes the weight of the wearer of said cleat over turf being walked on;

(b) flange attachment means extending from said upper surface of said flange for removably attaching said cleat to one of said sole attachment means of said sole of said shoe;

(c) a plurality of traction means extending from the opposing bottom surface of said flange, said flange distributing said weight over turf being walked on while said traction means provide traction against said turf; and

(d) said flange and said traction means having a combined profile of at most about 0.25 inch as measured from said upper surface of said flange to a bottom portion of a most downwardly extending portion of said traction means; wherein:

said cleat provides traction against the ground without doing damage to the turf surface being walked on and without puncturing golf turf.

²
~~18~~ (previously presented). The removable golf shoe cleat of claim ¹~~18~~ wherein said traction means comprise a resilient material.

³
~~20~~ (previously presented). The removable golf shoe cleat of claim ¹~~18~~ wherein said traction means comprise a durable plastic material.

⁴
~~21~~ (previously presented). The removable golf shoe cleat of claim ~~20~~³ wherein said durable plastic material comprises polyether block urethane.

⁵
~~22~~ (previously presented). The removable golf shoe cleat of claim ~~18~~¹ wherein said flange attachment means comprises a threaded stud extending from said upper surface of said flange of said cleat.

⁶
~~23~~ (previously presented). The removable golf shoe cleat of claim ~~22~~⁵ wherein:
said traction means extending from said opposing lower surface of said flange comprise ribs; and

each of said ribs has a maximum height between about 0.03125 inch and about 0.125 inch.

⁷
~~24~~ (previously presented). The removable golf shoe cleat of claim ~~23~~⁴ wherein each of said ribs has a length and a series of cross sections taken at different points along said length, each of said cross sections having a respective height, said respective heights varying along said length of said rib.

⁸
~~25~~ (previously presented). The removable golf shoe cleat of claim ~~18~~¹ wherein said opposing bottom surface of said flange has a convex shape.

26 – 34 (Canceled).